



# B-2 SERIES

## Standard Range

### Display / Bottom Mount

An innovative, self-learning, electronic controller gathers and automatically updates data of store closing times and quiet periods, ensuring optimal energy efficiency at all times.

**Options**  
Illuminated sign panel

Ability to operate as either perishable mode or non-perishable mode

Energy efficient long-life LED lights as standard

High speed energy efficient EC condenser fan motor

Fully removable electronically controlled cassette for easy servicing



Self-closing doors with double glazed, double Low/E, argon filled, toughened safety glass

Automatic energy saving mode

High ambient temperature performance

EMS Controller with fuzzy logic to ensure maximum energy efficiency

Lockable swivel castors

B1200-2



**Warranty**  
2 year protection




**High Energy Efficiency**


# Specifications

## B-2 Series

### Display / Bottom Mount



Integral top view



Integral front elevation


#### B600-2 - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	
<b>B600-2</b>	190	Integral	Chiller	<b>Gross Volume</b> 584 litres <b>Total Shelf Area</b> 1.62m <sup>2</sup> <b>Floor Area</b> 0.6m <sup>2</sup> (inc. 50mm stand-off)
		Integral		
		External (mm)	Internal (mm)	
<b>Height</b>	2005	1454		
<b>Width</b>	740	640		
<b>Depth</b>	758	602		
<b>Door Height</b>	1536			
<b>Glass Area</b>	0.92m <sup>2</sup>			


- 4.62 MEPS (kWh/24h/m<sup>2</sup>)
- Maximum height 2195mm with optional sign panel fitted
- +2°C to +4°C in 40°C ambient



**B600-2**  
1 DOOR



Integral top view



Integral front elevation

#### B1200-2 - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	
<b>B1200-2</b>	254	Integral	Chiller	<b>Gross Volume</b> 1079 litres <b>Total Shelf Area</b> 3m <sup>2</sup> <b>Floor Area</b> 1.03m <sup>2</sup> (inc. 50mm stand-off)
		Integral		
		External (mm)	Internal (mm)	
<b>Height</b>	2005	1454		
<b>Width</b>	1280	1180		
<b>Depth</b>	758	602		
<b>Door Height</b>	1536			
<b>Glass Area</b>	1.57m <sup>2</sup>			

- 6.29 MEPS (kWh/24h/m<sup>2</sup>)
- Maximum height 2195mm with optional sign panel fitted
- +2°C to +4°C in 40°C ambient



**B1200-2**  
2 DOOR